GT Mini 3330 Range



Easy Meet anyone, anywhere, anytime



Point-to-point Unlimited calling



HD voice & video Exceptional quality



Screen sharing Collaborate on content



Contacts Scroll and search directories and personal contacts



Guest invite Invite anyone to join you on video



QuickMeet™ Hold instant multiparty meetings



QuickConnect™ Plug and play installation



Call+ Transfer, hold, forward, call history and do not disturb



Favorites Speed dials with availability



Interoperable
Works with Cisco,
Skype for Business/
Lync, Lifesize, Polycom,
H.323/SIP



AV integration Modules for AMX, Extron and Crestron



Video mail Send and receive personal video messages



Join now
See today's meetings
and join instantly



Secure
Secure and certificatebased authentication



Auto upgrade Always on the latest version

EVERYTHING YOU NEED TO KNOW

A meeting room video conferencing hardware endpoint that allows you to match room size, budget and functionality. Choose between four options:

OPTION 1

HD USB camera and support for one screen



OPTION 2

HD USB camera and support for two screens



OPTION 3

Pan, tilt and zoom camera and support for one screen



OPTION 4

Pan, tilt and zoom camera and support for two screens





Highlights for your business

- Transforms any meeting space into a video conferencing room
- Cost-effective great quality solution
- Improves productivity and decision making
- Reduces costs and time spent traveling
- Intuitive and easy-to-use with no training needed
- Meet anyone on any device with unlimited guest invitations
- Extends business reach and works seamlessly with existing voice and video installations: Cisco, Skype for Business/Lync, Polycom, Lifesize, H.323, SIP, and phones
- Can be installed anywhere in minutes
- Rapid return on investment, with no need to purchase network infrastructure equipment

@ a Glance

- Systems for small, medium, large and very large rooms
- Complete solution includes advanced codec and choice of: touchscreen controller, camera, microphone
- · High-definition video
- Full duplex wideband audio
- Plug and play, auto configured installation
- Content sharing
- Meet anyone with Guest invite
- Seamless interoperability
- Connectivity for PC for local and remote PC presentation
- Advanced technology for packet loss resilience and low latency

TECHNICAL SPECIFICATIONS

Physical

Weight 2.5lbs/1.1kg Dimensions: (H x W X D) 1.6" x 14.2" x 4.3"/40mm x 365mm x 110mm

Power

External autosensing power supply – 100 – 240 VAC 50/60 Hz 1.5A

Audio and video I/O

1x HDMI in for camera input
1x Camera control port
1 x HDMI in for PTZ camera
1x USB for USB camera input
DVI-I in for PC input
2x HDMI out for 1080p60 displays
2x XLR for microphone input
1x Line in for PC stereo
audio in
1x Line out for stereo
audio out

Network interfaces

1x Autosensing 10/100/1000 Ethernet LAN (RJ-45) 1x StarLeaf touchscreen controller connection (RJ-45)

Protocols

EVSIP, H.323, SIP, H.239, RDP, Skype for Business/Lync (CCCP/ AVMCU), WebRTC, DTLS, BFCP

Codec support

Wideband audio with AAC-ELD, AAC-LD, G.711 µ-law / A-law, G.722, G.722.1, Annex C, iLBC, H.263, H.263+, H.264, SVC, DTMF, Microsoft H.264 SVC, VP8

Video support

Main video send and receive up to 720p60 Content send and receive at 1920 x 1080

Network

QoS – DiffServ/ToS

Security

Secure and certificate-based authentication

Installation

Plug and play with QuickConnectTM Automatic speed test