

Barco Healthcare

Medical solutions portfolio



About Barco

Focused on transforming the delivery of care, Barco connects healthcare professionals at every patient touchpoint, from the imaging room to radiology, through specialist consultations and in the surgical suite. We offer a network of medical imaging solutions that deliver the complete picture to support more informed decisions, when and where it matters most.



Diagnostic displays



More than a medical display

Increasing image volumes, the growing complexity of studies, and physical discomfort while reading are the three biggest challenges radiologists face today. That is the conclusion of a 2014 survey conducted by The MarkeTech Group. The solutions? Improved image guality (91%), a more efficient workflow (77%), and better display ergonomics (70%), as indicated by radiologists themselves.

We are able to provide capabilities that can improve the reading experience in all aspects: speed, accuracy, intuitiveness, flexibility and ergonomics. How? By offering a complete imaging solution - high-quality display, ultra-fast controller for fast image loading and manipulation and automated calibration & QA to ensure peak performance and uptime – in which all components function smoothly as a unified system.

Barco's integrated technology platform enables us to develop a unique set of Intuitive Workflow features resulting in increased reading accuracy and decreased reading time. Only Barco display systems offer this diagnostic toolset, which adds a new dimension to radiologists' workflow by streamlining frequent tasks with automated features. Designed to help you speed through your workload with ease, these builtin, easy-to-use functions appear at your command, seamlessly paving the way for effortless productivity and working comfort.

Intuitive Workflow tools line-up

Click icons for video >	PROFILES	SCREENSHOT	AAM	VIRTUALVIEW	SPOTVIEW	TOUCHPAD	DIMVIEW	SMARTCURSOR	FIND CURSOR		CLONEVIEW	DAISYCHAINING
Coronis Uniti	\checkmark	\checkmark	\checkmark	\checkmark	√ ³	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	
Coronis Fusion	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark^2	\checkmark^4	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
Coronis	\checkmark	\checkmark	✓ ⁵	\checkmark	\checkmark^1		\checkmark	\checkmark	\checkmark		\checkmark	
Nio Gray/Color	\checkmark	\checkmark		\checkmark	\checkmark		\checkmark	\checkmark	\checkmark		\checkmark	
Nio Color 5MP	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark		\checkmark	\checkmark	\checkmark		\checkmark	
Eonis	\checkmark	\checkmark		\checkmark			\checkmark	\checkmark	\checkmark		\checkmark	

MDCG-5221, MDCG-3221

Enables I-Luminate during SpotView

Luminance adjustment only; color profile switching only available on Coronis Uniti, Coronis Fusion and Nio Color 5MP

The Barco Touchpad also enables the Align tool on Coronis Fusion and Coronis Uniti

QAWeb Enterprise

Always a clear view



QAWeb Enterprise helps you manage quality and assure compliance of your expanding healthcare enterprise with less effort, lower cost, and complete confidence. This fully automated and secure system guarantees consistent image quality and uptime for all PACS display systems within your facility and across your enterprise.


What makes QAWeb so unique?

> Scalable: Powerful tools to manage workstations from anywhere, at anytime

- > Flexible: Customize policies to meet your quality requirements
- > Intuitive: Effortless compliance and smart reporting
- > Secure: Assured security and patient privacy



Wants and woes of healthcare IT managers



Read more



QAWeb Enterprise video

MDCC-4230, MDCC-4330, MDCC-4430, MDCC-6330, MDCC-6430 and MDCC-6530

Optional on 4MP and 6MP Coronis Fusion Displays




Coronis Fusion



The only diagnostic display system explicitly designed for both PACS and multimodality breast imaging. Unique in its representation of calibrated color and grayscales. Remarkable in its 2D and 3D capabilities. Capable of both static and dynamic imaging.

Your benefits

- > One display for all images to unify your workflow
- > 12% more pixels to display more or larger images
- > The brightest display on the market delivers exceptional brightness resulting in more JNDs
- > Proven 10% higher detection when scrolling digital breast tomosynthesis images¹
- > Up to 30% increased detection probability thanks to patented I-Luminate™ technology²
- > Optimized for the standard field of vision and low reflection to minimize eyefatigue
- > Intuitive workflow tools selectively dim/boost and focus light for closer inspection
- > Cleared for multimodality breast imaging, incl. breast tomosynthesis, 3D mammography, breast MRI, breast ultrasound, CT and ultrasound, including vascular and gynecological ultrasound







stresses. Optimized for an efficient workflow with clinical tools proven to increase accuracy and decrease reading times.

Your benefits


- > Bright, calibrated luminance of 600 cd/m2 for the lifetime of the display
- > Uniform luminance with patented Color PPU technology
- > High contrast of 2000:1 to see subtle image details
- > SteadyColor[™] calibration technology to see details in the important color content of images
- > Wide Gamut display
- > Wide viewing angle in your field of view
- > Higher brightness allows you to see more details with less eye strain
- > SoftGlow[™] task and wall lighting
- > Barco Optical Glass[™] reduces reflections and improves contrast
- > SpotView[™] to see more details in the image more guickly increased accuracy and decreased reading time
- > Auto QA and compliance tests meet the latest regional standards
- > Assure compliance and uptime of all your PACS workstations
- > Intervention-free QA saves time, reduces effort and cost

Models and options

Models and options

Coronis Fusion, perfected for color imaging with vivid and calibrated colors to help you see important color image details. Ergonomically designed to reduce repetitive

Coronis Fusion by numbers











A family of diagnostic displays ideal for high-quality imaging of diagnostic modalities. Engineered down to the smallest detail to ensure perfect luminance and DICOM compliance.

Your benefits

- > The brightest 3MP display on the market exceeding ACR guidelines
- > Exceptional local contrast optimized for faster reading
- > Subtle details are more conspicuous for easy detection (Per Pixel Uniformity)
- > Real-time intervention-free calibration and QA
- > Factory-fit glass front cover reduces reflections (<0.5%)
- > Comes with I-Luminate to aid in seeing subtle image details

A family of diagnostic displays that bring dependable diagnostic imaging to its true potential. Nio's proven technologies ensure diagnostic confidence at all times, making it the standard for the radiology reading room.

Your benefits

- > Most efficient dual-head option on the market
- > Highest brightness and contrast luminance ratio exceeds ACR guidelines
- > Minimal image manipulations less windowing, leveling, zooming & panning
- > More DICOM JNDs to see more subtle details quicker
- > Uniform image rendering center to edge
- > Factory-fit front cover reduces reflection and improves visible contrast


More screen, more mammo Nio Color 5MP



				DIAGNOSTIC	DISPLAYS				
	2MP	3MP		4MP	5MP			6MP	12MP
	MDNC-2221	MDNC-3421	MDCG-3221	MDCC-4430	MDNG-5221	MDNC-6221	MDCG-5221	MDCC-6530	MDMC-12133
SPECIFICATIONS	Nio Color 2MP	Nio Color 3MP	Coronis 3MP	Coronis Fusion 4MP	Nio 5MP	Nio Color 5MP	Coronis 5MP	Coronis Fusion 6MP	Coronis Uniti®
Varranty	5 years	5 years	5 years	5 years	5 years	5 years	5 years	5 years	5 years
Active screen size (H x V)	432 x 324 mm (17.0 x 12.8")	433 x 325 mm (17.0 x 12.8")	325 mm x 433 mm (12.8" x 17.1")	655 x 410 mm (25.8 x 16.1")	422.4 mm x 337.9 mm (16.5 x 13.3")	433 x 325 mm (17 x 12.8")	422.4 mm x 337.9 mm (16.5 x 13.3")	654 x 409 mm (25.8 x 16.1")	708.1 x 472.1 mm (27.8 x 18.6")
Screen echnology	TFT AM Color LCD IPS	TFT AM Color LCD IPS	UA-SFT (Ultra Advanced Super Fine Technology)	IPS-TFT color LCD	a-si TFT active matrix dual domain IPS	a-si TFT active matrix dual domain IPS	a-si TFT active matrix dual domain IPS	IPS-TFT color LCD	IPS
Diagonal size	540 mm (21.3")	540 mm (21.3")	540 mm (21.3")	772 mm (30.4")	540 mm (21.3")	540 mm (21.3")	540 mm (21.3")	772 mm (30.4")	853.44 mm (33.6")
Aspect ratio	4:3	4:3	4:3	16:10	5:4	3:4	5:4	16:10	3:2
Native resolution	2MP (1600 x 1200)	3MP (2048 x 1536)	3MP (2048 x 1536)	4MP (2560 x 1600)	5MP (2560 x 2048)	5.8MP (2100 x 2800)	5MP (2560 x 2048)	Native 6MP (3280 x 2048) Configurable to 2 x 3MP+ (1640 X 2048) Configurable to 2 x 3MP (1536 X 2048)	4200 x 2800
Luminance (DICOM calibrated)	800 cd/m² (400 cd/m²)	900 cd/m² (500 cd/m²)	1700 cd/m² (600 cd/m²)	1050 cd/m ² (600 cd/m ²)	1020 cd/m ² (500 cd/m ²)	1000 cd/m ² (600 cd/m ²)	1200 cd/m ² (600 cd/m ²)	1050 cd/m ² (600 cd/m ²)	2100 cd/m² (1000 cd/m²)
Contrast ratio	1400:1	1400:1	1400:1	2000:1	1200:1	1400:1	1200:1	2000:1	1200:1
Screen protection	Factory fit protective, non-reflective glass cover	Factory fit protective, non-reflective glass cover	Factory fit protective, non-reflective glass cover	Factory fit protective, non-reflective glass cover	Factory fit protective, non-reflective glass cover	Factory fit protective, non-reflective glass cover	Factory fit protective, non-reflective glass cover	Factory fit protective, non-reflective glass cover	Factory fit protective, non-reflective glass cover
Sensor technology		Integrated front-of-screen sensor, BLOS, ALC presets	Integrated I-Guard front- of-screen photometer sensor, Intelligent Multi- Sensor Technology, ALC	Integrated I-Guard front-of- screen color sensor, Intelligent Multi-Sensor Technology, ALC	Integrated front-of- screen sensor, BLOS, ALC	Integrated front-of-screen sensor, BLOS, ALC	Integrated I-Guard front- of-screen photometer sensor, ALC	Integrated I-Guard front- of-screen photometer sensor, Intelligent Multi- Sensor Technology, ALC	Integrated color I-Guard front-of-screen photom- eter sensor, Intelligent Multi-Sensor Technology, ALC
Diagnostic imaging technology	ULT, MXRT, Intuitive Workflow Tools	ULT, MXRT, Intuitive Workflow Tools	PPU, DuraLight, MXRT, Intuitive Workflow Tools	SteadyColor, Color PPU, SmoothGray, MXRT, Intuitive Workflow Tools with optional touchpad	ULT, MXRT, Intuitive Workflow Tools	ULT, MXRT, Intuitive Workflow Tools, Steady- Color, SteadyGray	PPU, SmoothGray, DuraLight, I-Luminate, MXRT, Intuitive Workflow Tools	SteadyColor, Color PPU, SmoothGray, MXRT, Intui- tive Workflow Tools with optional touchpad	SteadyColor, Color PPU, I-Luminate, RapidFrame, SmoothGray, DuraLight, Clear/ BlueBase, SoftGlow, Filmclip, MXRT, Intuitive Workflow Tools with Touchpad
/ideo input signals	DVI-D Dual Link, DisplayPort	DVI-D Dual Link, DisplayPort	DVI-D Dual Link, DisplayPort	DisplayPort 1.2 (2x)	DVI-D Dual Link, DisplayPort	DVI-D Dual Link, Display- Port	DVI-D Dual Link, DisplayPort	DisplayPort 1.2 (x2	DisplayPort 1.2
Medical device regulations	FDA (510)k: Digital Radiography Class II EC: Diagnostic or therapeutical radiology, Class IIb	FDA (510)k: Digital Radiography Class II EC: Diagnostic or therapeuti- cal radiology, Class IIb	FDA (510)k: Digital Radiography Class II EC: Diagnostic or therapeuti- cal radiology, Class IIb	FDA (510)k: Digital Radiography Class II EC: Diagnostic or therapeutical radiology, Class IIb	FDA (510)k Digital Radiography & Mammography Class II EC: Diagnostic or therapeuti- cal radiology, Class IIb	FDA (510)k: Digital Radiogra- phy & Mammography Class II, including breast tomosyn- thesis EC: Diagnostic or therapeutical radiology, Class IIb	FDA (510)k: Digital Radiography & Mammography Class II EC: Diagnostic or therapeuti- cal radiology, Class IIb	FDA (510)k: Digital Radiography Class II EC: Diagnostic or therapeuti- cal radiology, Class IIb	FDA (510)k: Digital Radiography multi-modality breast imaging, incl. breast tomosynthesis, 3D mammography, breast MRI, breast ultrasound, CT and ultra- sound, including vascular and gynecological ultrasound Class II
Package includes	Nio display system, MXRT graphics controller, Intuitive Workflow toolset, 5-year all- inclusive warranty, QAWeb	Nio display system, MXRT graphics controller, Intuitive Workflow toolset, 5-year all- inclusive warranty, QAWeb	Coronis diagnostic display system, MXRT graphics controller, Intuitive Workflow toolset, 5-year all-inclusive warranty, QAWeb	Coronis Fusion diagnostic display system, MXRT graphics controller, Intuitive Workflow toolset, 5-year all-inclusive warranty, QAWeb	Nio display system, MXRT graphics controller, Intuitive Workflow toolset, 5-year all- inclusive warranty, QAWeb	Nio display system, MXRT graphics controller, Intuitive Workflow toolset, 5-year all-inclusive war- ranty, QAWeb	Coronis diagnostic display system, MXRT graphics con- troller, Intuitive Workflow toolset, 5-year all-inclusive warranty, QAWeb	Coronis Fusion diagnos- tic display system, MXRT graphics controller, Intuitive Workflow toolset, 5-year all- inclusive warranty, QAWeb	EC: Diagnostic or therapeutica radiology, Class IIb Coronis Uniti diagnostic display system, MXRT graphics controller, Intuitive Workflow toolset, SoftGlow keyboard and wall light, Touchpad and film clip
Options	Additional MXRT graphics controller options, QAWeb Premium, Extended and Advanced Warranty	Additional MXRT graphics controller options, QAWeb Premium, Extended and Advanced Warranty	Additional MXRT graphics controller options, QAWeb Premium, Extended and Advanced Warranty	Additional MXRT graphics controller options, QAWeb Pre- mium, Extended and Advanced Warranty	Additional MXRT graphics controller options, QAWeb Premium, Extended and Advanced Warranty	Additional MXRT graphics controller options, QAWeb Premium, Extended and Advanced Warranty	Additional MXRT graphics controller options, QAWeb Premium, Extended and Advanced Warranty	Additional MXRT graphics controller options, QAWeb Premium, Extended and Advanced Warranty	Extended and Advanced Warranty, DisplayCare with premium QAWeb feature

Clinical displays







A family of clinical displays for use in key clinical specialties and dental practices. Eonis delivers unmatched image consistency – providing healthcare professionals with consistent images, wherever they are – to make collaboration between specialists easier. Eonis displays can be managed centrally with QAWeb.

Your benefits

- > Designed and approved for hospital and dental environments
- > Ambient Light pre-sets for dark rooms, offices and the OR
- Supports efficient inter-disciplinary collaboration with consistent quality controlled images
- > Cleanable displays for infection control (70% alcohol-based cleaning agents), safe for near-patient use
- > Efficient and intelligent enterprise IT workflow thanks to a built-in sensor with software tool to manage quality and assets
- > Lowest cost-of-ownership over time without a need for capital budget

EMR other

Eonis put to the test



Eonis vs consumer displays



Are you a dentist working in Germany?

Visit www.barco.com/de/dental to find a solution that complies with the DIN 6868-157 standard.

			CI	.INICAL DISPLAY	S		
	MDRC-1219 (TS)	MDRC-2321	MDRC-2222, Option TS	MDRC-2222, Option BL	MDRC-2222, Option WP	MDRC-2324, Option BL	MDRC-2324, Option WI
SPECIFICATIONS	MDRC-1219 (TS)	Eonis 21"	Eonis 22" touch	Eonis 22" black	Eonis 22" white	Eonis 24" black	Eonis 24" white
Warranty	3 years	3 years	3 years	3 years	3 years	3 years	3 years
Active screen size	376 x 301 mm (14.81 x 11.85")	432 mm x 324 mm (17" x 12.76")	476 mm x 268 mm (18.7" x 10.5")	476 mm x 268 mm (18.7" x 10.5")	476 mm x 268 mm (18.7" x 10.5")	518.4 mm x 324.0 mm (20.41" x 12.76")	518.4 mm x 324.0 mm (20.41" x 12.76")
Screen technology	IPS-TFT Color LCD	TFT Color LCD	TFT Color LCD IPS				
Diagonal size	482 mm (19")	541 mm (21.3")	546 mm (21.5")	546 mm (21.5")	546 mm (21.5")	609.6 mm (24.0")	609.6 mm (24.0")
Aspect ratio	5:4	4:3	16:9	16:9	16:9	16:10	16:10
Native resolution	1MP (1280 x 1024)	2MP (1600 x 1200)	2MP (1920 × 1080)	2MP (1920 × 1080)	2MP (1920 × 1080)	2MP (1920 x 1200)	2MP (1920 x 1200)
Luminance (DICOM calibrated)	330 cd/m² (250 cd/m²)	440 cd/m² (250 cd/m²)	300 cd/m² (180 cd/m²)				
Contrast ratio	1000:1	1500:1	1000:1	1000:1	1000:1	1000:1	1000:1
Screen protection	n/a	n/a	Protective, non-reflective glass cover	n/a	Protective, non-reflective glass cover	n/a	Protective, non-reflective glass cover
Front sensor technology	Front consistency sensor	Front consistency sensor	Front consistency sensor	Front consistency sensor	Front consistency sensor	Front consistency sensor	Front consistency sense
Cleanability	n/a	n/a	n/a	n/a	IP32	n/a	IP32
Video input signals	DisplayPort, DVI	DisplayPort, DVI	DisplayPort, DVI-I				
Medical device regulations	FDA & EC: Viewing of medical radiology images (Class I)	FDA & EC: Viewing of medical radiology images (Class I)	FDA & EC: Viewing of medical radiology images (Class I)	FDA & EC: Viewing of medical radiology images (Class I)	FDA & EC: Viewing of medical radiology images (Class I)	FDA & EC: Viewing of medical radiology images (Class I)	FDA & EC: Viewing of medical radiology images (Class I)
Package includes	 MDRC display 3-year all-inclusive warranty QAWeb 	 Eonis display 3-year all-inclusive warranty QAWeb 	 Eonis display 3-year all-inclusive warranty QAWeb 	 Eonis display 3-year all-inclusive warranty QAWeb 	 Eonis display 3-year all-inclusive warranty QAWeb 	 Eonis display 3-year all-inclusive warranty QAWeb 	 Eonis display 3-year all-inclusive warranty QAWeb
Options	 MXRT graphics controller Intuitive Workflow toolset DisplayCare with QAWeb premium features 	 MXRT graphics controller Intuitive Workflow toolset QAWeb Premium 	 MXRT graphics controller Intuitive Workflow toolset QAWeb Premium 	 MXRT graphics controller Intuitive Workflow toolset QAWeb Premium 	 MXRT graphics controller Intuitive Workflow toolset QAWeb Premium 	 MXRT graphics controller Intuitive Workflow toolset QAWeb Premium 	 MXRT graphics controller Intuitive Workflow toolset QAWeb Premium

Option WP



' white

324.0 mm 12.76")

n (24.0″)

) x 1200)

180 cd/m²)

):1

on-reflective cover

ency sensor

rt, DVI-I

s controller flow toolset um

Surgical displays



surgery



A family of surgical displays designed for real-time critical imaging in the operating room. The portfolio comprises near-patient and large-screen displays for use in any environment where surgical procedures are carried out, including the endoscopy room, interventional suite or hybrid OR. Available in high definition or 4K ultra-high definition.

Your benefits


- > Deep blacks and accurate colors from any viewing angle
- > 4:4:4 chroma subsampling for impeccable color accuracy
- > Near-zero latency provides perfect surgical hand-eye coordination
- > Improved visualization in high ambient light environments
- > Backlight output stabilization guarantees image stability and brightness over the lifetime of the display
- > Cleanable infection control design complies with strict OR hygiene standards
- > Unique cable management system makes it easy to install and disinfect
- > Automated failover feature so a backup signal is always available
- > Perfect match with Barco's Nexxis OR-over-IP platform for full OR integration

4 ways 4K changes surgical imaging:



SURGICAL DISPLAYS

ENDOSCOPY DISPLAYS







SPECIFICATIONS	AMM 215WTD	MDSC-2324	MDSC-2326	MDSC-2326 High Bright	MDSC-2232	MDSC-8231	MDSC-2242	MDSC-8255
Warranty	18 months	3 years	3 years	3 years	3 years	3 years	3 years	3 years
Active screen size (H x V)	475 x 267 mm (18.7 x 10.5")	518.4 x 324 mm (20.4" x 12.7")	576 x 324 mm (22.7" x 12.8")	576 x 324 mm (22.7" x 12.8")	698 x 393 mm (27.48" x 15.47")	698 x 368 mm (27.48" x 14.49")	930 x 523 mm (36.6″ x 20.6")	1210 x 640 mm
Screen technology	TFT AM LCD / LED Backlight	TFT AM LCD / S-IPS technology / LED backlight	TFT AM LCD / IPS-PRO / LED backlight	TFT AM LCD / IPS-PRO / LED backlight	TFT AM LCD / S-IPS technology / LED backlight	TFT AM LCD / IPS-PRO technology / LED backlight	TFT AM LCD / LED backlight	TFT AM LCD / IPS technology / LED backlight
Diagonal size	21.46" (545.2 mm)	24" (611.3 mm)	26" (661 mm)	26" (661 mm)	31.55" (801 mm)	31" (789 mm)	42" (1067 mm)	54.6" (1388 mm)
Aspect ratio	16:9	16:10	16:9	16:9	16:9	17:9	16:9	16:9
Native resolution	Full HD 1920 x 1080	WUXGA 1920 x 1200	Full HD 1920 x 1080	Full HD 1920 x 1080	Full HD 1920 x 1080	4K-2K UHD 4096 x 2160	Full HD 1920 x 1080	4K UHD 3840 x 2160
Luminance	250 cd/m ²	400 cd/m ²	500 cd/m ²	900 cd/m ²	450 cd/m ²	550 cd/m ²	500 cd/m ²	500 cd/m ²
Contrast ratio	1000:1	1500:1	1400:1	1400:1	1300:1	1400:1	4000:1	1000:1
Screen protection	Double-side anti-reflective PMMA protective cover	Double-side anti- reflective PMMA protective cover	Scratch-resistant 2-side anti-reflective alkali-aluminosilicate glass cover	Scratch-resistant 2-side anti-reflective alkali-aluminosilicate glass cover	Double side anti- reflective tempered glass protective cover	Scratch-resistant 2-side anti-reflective alkali-alu- minosilicate glass cover	Double side anti-re- flective tempered glass protective cover	Scratch-resistant, 2-side anti-reflective glass cover
Cable management	n/a	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Cleanability	IP21 (IPx5 front)	IP21 (IP45 front)	IP21 (IP45 front side)	IP21 (IP45 front side)	IP20 (IP45 front side only)	IP20 (IP45 front side only)	IP21 (IPx5 front side only)	IP20 (IP45 front side)
Failover	n/a	Yes	Yes	Yes	Yes	Yes	Yes	n/a
Video input signals	2xDVI-I, VGA, RGBS / YPbPr, S-video, Composite video, 3G-SDI	DVI-I Single-Link (Digital & Analog / HDMI sup- port with HDCP), Com- ponent Video RGBS / YPbPr (4xBNC) / S-video / Composite video / 3G- SDI / DisplayPort v 1.1a Optional: integrated Nexxis network adapter	DVI-I (HDMI sup- port), RGBS / YPbPr, S-video, Composite video, 3G-SDI, Dis- playPort (1.1a) Optional: integrated Nexxis MNA-120 net- work adapter / 2nd DVI / 2nd SDI	DVI-I (HDMI support), DVI-D, 2x 3G-SDI, RGBS / YPbPr, S- video, Composite video, DisplayPort 1.1a Optional: integrated Nexxis MNA-120 decoder	DVI-I (2x - HDMI support), RGBS / YPbPr, S-video, Composite video, 3G-SDI (2x), Dis- playPort (1.1a) Optional: integrated Nexxis MNA-120 network adapter	2x DP 1.1, 1x DP 1.2 MST, 2x HDMI 2.0 1x DVI, 1x 3G-SDI Optional: integrated Nexxis MNA-240 network adapter	DVI-I (HDMI support), RGBS / YPbPr, S-video, Composite video, 3G-SDI, DisplayPort (1.1a) Optional: integrated Nexxis MNA-120 network adapter	2x DP 1.1, 1x DP 1.2 MST, 2x HDMI 2.0 1x DVI, 1x 3G-SDI Optional: 2x FO SFP+ module for 4K-UHD Nexxis link
Video output signal	SDI / S-video / Composite Video, RGBS / YPbPr	DVI-D / S-video / Composite video / 3G-SDI	DVI / S-video / 3G-SDI / Composite	DVI-D / 2x 3G-SDI / S-video / Composite	DVI / SDI / S-video / Composite	DVI (UHD downscaled) 3G-SDI (input loop- through)	DVI / SDI / S-video / Composite	DVI (UHD downscaled) 3G-SDI (input loop- through)
Medical device regulations	FDA & EC: Endoscopic and Surgical imaging (Class I)	FDA & EC: Endoscopic and Surgical imaging (Class I)	FDA & EC: Endoscopic and Surgical imaging (Class I)	FDA & EC: Endoscopic and Surgical imaging (Class I)	FDA & EC: Endoscopic and Surgical imaging (Class I)	FDA & EC: Endoscopic and Surgical imaging (Class I)	FDA & EC: Endoscopic and Surgical imaging (Class I)	FDA & EC: Endoscopic and Surgi- cal imaging (Class I)
Package includes:	 AMM 215WTD display 18-month all- inclusive warranty 	 MDSC display 3-year all-inclusive warranty 	 MDSC display 3-year all-inclusive warranty 	 MDSC display 3-year all-inclusive warranty 	 MDSC display 3-year all-inclusive warranty 	 MDSC display 3-year all-inclusive warranty 	 MDSC display 3-year all-inclusive warranty 	 MDSC display 3-year all-inclusive warranty
Options	 Ask about our different model options and associ- ated accessories Core+ warranty 	 Ask about our different model options and associated accessories Core+ warranty 	 Ask about our different model options and associated accessories Core+ warranty 	 Ask about our different model options and associated accessories Core+ warranty 	 Ask about our different model options and associated accessories Core+ warranty 	 Ask about our different model options and associated accessories Core+ warranty 	 Ask about our different model options and associated accessories Core+ warranty 	 Ask about our different model options and associated accessories Core+ warranty

Core+ warranty

Core+ warranty



MDSC-8358

2 years

1270 x 721.5 mm (50 x 28.4")

a-si TFT active matrix

58" (1473 mm)

16:9

4K UHD 3840 x 2160

700 cd/m²

4000:1

ide Double side antireflective laminated glass protective cover

Yes

IP20 (IP21 with protective glass)

Yes

AST, DVI Dual Link, DVI Single Link, DP1.2 Optional: Nexxis MNA-240 decoder, 2x Single Link DVI Dual Splitter

n/a

FDA & EC: Endoscopic and Surgical imaging (Class I)

 MDSC display • 2-year all-inclusive warranty

• Ask about our different • Ask about our different model options and associated accessories 25

Core+ warranty



MDSC-8427

3 years

597 x 336 mm (23.5" x 13.2")

TFT AM LCD / IPS-PRO technology / LED backlight

27" (685 mm)

16:9

4K UHD 3840 x 2160

750 cd/m²

1400:1

Scratch-resistant 2-side anti-reflective alkali-aluminosilicate glass cover

Yes

IP21 (IP45 front side)

Yes

2x DP 1.1, 1x DP 1.2 MST, 2x HDMI 2.0 1x DVI, 1x 3G-SDI Optional: integrated Nexxis MNA-240 network adapter

DVI (UHD downscaled) 3G-SDI (input loopthrough)

FDA & EC: Endoscopic and Surgical imaging (Class I)

 MDSC display • 3-year all-inclusive warranty

model options and associated accessories

Core+ warranty

Smart displays and user interfaces

EMR surgery other





A range of displays that offer an intuitive, ergonomic touch experience, specially designed for use in a medical environment. They can be used for a variety of applications, including the digital operating room and medical carts. Wherever clinicians need access to detailed information, at the touch of a fingertip.

Your benefits

- > Multi- and single-touch functionality for quick operation
- > Ergonomic interaction, even when wearing gloves
- > Fit for use in highly demanding, mission-critical environments
- > Special design that allows for easy cleaning and infection control
- > Easy to install, whether on carts, arms or booms

Smart displays and user interfaces

SMART DISPLAYS AND USER INTERFACES

SPECIFICATIONS	MDRC-2222, Option TS	MDRC-1219, Option TS	AMM 215WTTP	MUIP-2112
Warranty	3 years	3 years	18 months	2 years
Active screen size	476 x 268 mm (18.7" x 10.5")	376 x 301 mm (14.8" x 11.8")	476 x 267 mm (18.7" x 10.5")	276 x 157 mm (10.8" x 6.2")
Screen technology	TFT Color LCD IPS	IPS-TFT Color LCD	TFT AM LCD	TFT AM LCD
Diagonal size	21.5" (546 mm)	19" (482 mm)	21.5" (545 mm)	12.5" (317 mm)
Aspect ratio	16:9	5:4	16:9	16:9
Native resolution	2MP (1920 x 1080)	1MP (1280 x 1024)	2MP (1920 x 1080)	2MP (1920 x 1080)
Luminance	300 cd/m ²	330 cd/m ²	250 cd/m ²	400 cd/m ²
Contrast ratio	1000:1	1000:1	1000:1	1000:1
Screen protection	Protective, non-reflec- tive glass cover	N/A	N/A	Anti Glare (Gloss 50)
Cleanability	N/A	N/A	N/A	IP54 (with sealed con- nector cover)
Video input signals	DisplayPort, DVI-I	DVI, DisplayPort	DVI-D, VGA	N/A
Medical device regulations	FDA & EC: Viewing of medical radiology images (Class I)	FDA & EC: Viewing of medical radiology images (Class I)	FDA & EC: Endoscopic and Surgical imaging (Class I)	Medical device, class 1

Barco technologies that make a difference



I-Guard[™] front sensor

This integrated, patented front-of-screen photometer has become the industrystandard technology for monitoring image quality and DICOM consistency. The new generation of I-Guard has been improved to measure much finer gradations of colors spread over the color gamut of the display. Combined with Barco's QAWeb service, it provides an easy-to-use tool for calibration and Quality Assurance.

Benefits

- > Worry-free DICOM accuracy
- > Continuous, automated QA of the entire optical stack
- > Remote assessment of your display's image quality

Ambient Light **Compensation[™]** (ALC)

Ensures that your diagnostic display system remains DICOM compliant under all lighting conditions by monitoring display brightness compared to the ambient light level in the room. In combination with QAWeb, ALC warns you when the ambient light level exceeds a predefined threshold.

Benefits

LCD panels typically suffer from nonuniform behavior across more than 25% of the screen area, causing noise in the image. ULT eliminates those luminance and color non-uniformities, making sure that your display is compliant with DICOM GSDF across the entire screen area.

Uniform Luminance

Technology[™] (ULT)

Benefits

- > Uniform luminance across the entire screen
- > Perfect DICOM compliance from center to corner

Benefits

- > Reduced screen noise
- > Improved contrast and accuracy in fine details
- > Improved image quality at a lower dose to the patient

Without PPU

Benefits

- > Improved reading productivity
- studies
- > Reduced eye fatigue



I-Guard video

With I-Guard



> DICOM compliance under all


> Optimal image quality in every

environment so no detail goes

lighting conditions

unnoticed

DICOM compliance under all lighting conditions thanks to ALC



Without ULT

With ULT

ULT technology highlight



With PPU



Coronis Fusion video




Fusion

Measures and adjusts the luminance of each pixel and makes it permanently DICOM compliant. As such, PPU eliminates screen noise, ensuring consistent colors and grayscales.

Color Per Pixel

Uniformity[™] (PPU)



Barco Optical glass[™]

'Fusion' design replaces a dual-head display setup by a single, large-screen monitor without a hindering central bezel. It allows you to place more images on the screen - just the way you want which has proven to increase productivity by up to 19% and reduce eye strain.

Reduces reflection, enhances image sharpness and viewing comfort. The multi-coated glass is highly durable, scratch-resistant, and protects the LCD panel from physical damage. A protective front cover - available on all Barco displays – further enhances the diagnostic experience.

Benefits

- > Protection of your valuable LCD panel
- > Improved image contrast & minimal reflections
- > Easy and safe cleaning





Optical glass technology highlight



> Easy side-by-side comparison of

IPS-Pro

RapidFrame[™]

I-Luminate[™]

A breakthrough LCD architecture offering a significantly wider viewing angle than competing LCD technologies. It ensures images are displayed more accurately and with a higher contrast ratio near the sides of the display. With IPS-Pro, the viewing angle is 120°, which is nearly twice the value achieved by other technologies.

For high-speed cine imaging without blur when reviewing multi-frame image sequences - such as tomosynthesis, breast ultrasound and breast MRI - or when hovering over the image with the magnifying glass. RapidFrame technology counteracts motion blur by providing a high pixel refresh rate.

This brightness boost system has proven to increase detection of microcalcifications by up to 30%! Simply push the I-Luminate™ 'hot light' button to temporarily boost your display brightness. Combined with Barco's handy film clip, I-Luminate allows you to compare studies with film-based priors on the display.

Benefits

- > Superior diagnostic accuracy
- > Wider viewing angle improves multiuser viewing

Benefits

- > High-speed cine imaging without blur for fast interpretation
- > Increased screening efficiency due to highly efficient diagnostic workflow

Benefits

- > Enhanced perception of small and low contrast details
- > Simplified comparison with filmbased studies
- > Uninterrupted DICOM-compliance





		→←		

RapidFrame video



SteadyColor[™] & **SteadyGray**[™]

Around 90% of images generated are now in color and color is often used for additional functionality (e.g. combining Doppler images with ultrasound). In order to guarantee consistent, perceptually linear color and still meet the DICOM standard for grayscales, SteadyColor executes advanced calibration for both grayscale and all Just Noticeable Differences (JNDs). This is achieved using multiple sensors in combination with numerous 3D Look-Up Tables (LUTs). SteadyGray uses the same color calibration technology to achieve a more constant and consistent gray appearance.

Benefits


- > Maximize the diagnostic value of color in images
- > Maintain image quality and DICOM compliance under all lighting conditions

SpotView[™]

SpotView creates a bright focal point on the screen, enhancing brightness and contrast inside a circular region of interest while dimming the surrounding image area. This heightens visibility of subtle differences in the image. With SpotView Mag, you can even double the size of the image so no detail goes unnoticed. There's a proven increase in accuracy and decrease in reading time.

Benefits


- > Better visibility of subtle differ ences in the image
- > Extremely helpful when viewing pediatric extremities, breast calcifications and chest exams



SpotView

SpotView video

SteadyColor technology highlight



Watch video







DimView[™]

DimView automatically dims the auxiliary displays used for patient worklists or dictation, reducing peripheral ambient light during readings so the eye can better focus on details on the diagnostic display.

Benefits

- > Improved focus on the main display, no distractions
- > More ergonomic reading experience





DimView video





SmartCursor[™]/ FindCursor™

VirtualView[™]

The use of multiple resolution displays in VirtualView provides radiologists with a PACS workstation results in the cursor a virtual navigational head on the main often getting stuck traveling from one display. It appears and disappears on user display to another, if you can even locate command, allowing you to add or remove the cursor in the first place. SmartCursor this screen content at your convenience.

Conference CloneView software is a high-performance, easy-to-use tool for projecting medical images from a diagnostic display onto a large screen,

especially useful in classroom settings.

Conference

CloneView[™]

Application Appearance Manager™

Application Appearance Manager allows you to individually manage the color profile and luminance of each application window so content appears as intended.

User Profiles creates a custom profile, set per modality and per user. It enables

X-ray images and hig

Benefits

a highlighted circle.

N

> Avoid losing time locating or moving the mouse cursor

maps the cursor to the correct places in the adjacent display. FindCursor indicates the location of the cursor with

- > Smoother and faster workflow
- > View other screen content more comfortably
- > Ideal for viewing worklists, re search, dictation, or ancillary tasks
- > Reduce the number of displays needed; simplify the desktop



- **Benefits**
- > High-quality cloned image without losing pixel precision
- > Fosters collaboration between peers
- > Ideal during multi-disciplinary team meetings



Benefits

- > Seamlessly integrate color (e.g. color photos) into the diagnostic workflow
- > Manage the luminance of applica tion windows depending on image content

Benefits

- > Read images according to your own preferences
- > Automatically get the right display settings for every modality



SmartCursor / FindCursor video



Watch video

VirtualView video




Watch video











User Profiles

SingleView™

a quick environment switch for image type, such as a lower luminance for

SingleView enables the use of the entire display as one display, and eliminates any tearing down the center of the display.

Benefits

- > More flexible desktop where im ages can be placed in the center of the screen
- > More ergonomic viewing experience



Screenshot

Capturing ideal images for meetings and review, this tool enables you to take a screenshot of what is currently in focus.

Benefits

- > Easy to communicate and share images and data
- > Fosters easy collaboration between peers





Icon overview

Find the medical display solution you need in just two clicks!



About Barco Healthcare

Improving the quality and value of care are the leading priorities for healthcare professionals today. At a time when the amount of data is growing rapidly and there is more demand for mobility, healthcare systems struggle to work more efficiently, and to provide personalized care to a growing number of patients in an affordable way.

Focused on transforming the delivery of care, Barco connects healthcare professionals at every patient touch point, from the imaging room, to radiology, through specialist consultations and in the surgical suite. We offer a network of medical imaging solutions that deliver the complete picture to support more informed decisions, when and where it matters most.

It's why we are considered the gold standard for medical visualization and how we are there at every stage of the patients' journey. So healthcare professionals can focus on patients' needs and, in the end, achieve the best clinical outcome.

Barco, enabling bright outcomes

¹ Marchessoux, C., et al. (2011). Validation of a new digital breast tomosynthesis medical display. Proceedings of SPIE, 7966, 79660R

² Kimpe, T. R. & Xthona, A. (2012). Quantification of detection probability of microcalcifications at increased display luminance levels. , Breast Imaging, Springer 7361, 490-497.

³ Mony Weschler, Montefiore Medical Center, 2012

M00193-R22-1019-PC October 2019

© 2019 Barco NV. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check www.barco.com for the latest specifications.

BARCO